



Length and Part number:

No	Part No:	Length (MM)
1	KC-974	2000±30
2	KC-976	3000±35
3	KC-978	5000±50

- NOTE:
- 1.100% OPEN & SHORT WIRE TEST;
 - 2.CONTACT RESISTANCE 2ohm Max;
 - 3.INSULATION RESISTANCE 10M ohm
- Min;
- 4.HI-POT DC 300V;

6		SCREW ϕ 4.0*L: 25MM	1PCS	
5		PVC 50P BLACK	30G	
4		PE	10G	
3		TYPE C-3.0 MALE BLACK AU:G/F	1PCS	
2		USB(3.0) A TYPE Male Connector G/F Color Blue	1SET	
1		UL20276 (USB3.0) (1P#28+DAM)*2C+2C#24+1P#28+AEB(AL) OD: 6.5MM Color BLACK	1PCS	
NO.	MATERIAL.P/N	DESCRIPTION	Q'TY	VENDOR

PRODUCT:	USB 3.0 A MALE TO TYPE-C MALE WITH SCREW CABLE
----------	--

REV:	A	UNIT:	mm	DRW BY	
SCALE:	N:1	DATE:	01-05-2025	HARSHIL	

QTY	VENDOR	QUALITY SYMBOLS
		☐ : ☒ :
		CRITICAL MAJOR
		∇ : ∇ : ZERO DEFECT S.P.C
		APPROVER

Tolerance x. ±0.60 .x ±0.40 .xx ±0.25  						
	REV:	A	UNIT:	mm	DRW BY	
	SCALE:	N:1	DATE:	01-05-2025	HARSHIL	
	BALAJI MICROTECHNOLOGIES PVT. LTD. (BMT) www.balaji-microtechnologies.com					



BALAJI MICROTECHNOLOGIES PVT. LTD. (BMT)
www.balaji-microtechnologies.com