



PIN ASSIGNMENT

P1	P2	WIRE
1	8	WHITE ORANGE
2	6	ORANGE
3	7	WHITE GREEN
4	3	GREEN
SHELL		SHELL

Length and Part number:

No	Part No:	Length (MM)
1	KC-986	2000±30
2	KC-988	3000±35
3	KC-990	5000±50

NOTES:

1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
2. CONDUCTOR RESISTANCE: 5 OHMS MAX.
3. INSULATOR RESISTANCE: 1M OHMS MIN, DC 300V 0.01sec.

5	PE	PE	NA
4	OVERMOLD	BLACK PVC 45P	NA
3	CONN	RJ45 CONNECTOR,8P8C.WITH SHELL	1PCS
2	CONN	M12-4P Male D-Coded Connector(B10-M120104D-01)	1PCS
1	CABLE	CAT6 26AWG*2P SFTP,JACKET:PVC COLOR:Black, OD= 6.0mm	1PCS
ITEM	PART NAME	DESCRIPTION	QTYT

PRODUCT: RJ-45 TO M12-4P D-CODED INDUSTRIAL CAMERA CABLE

											
DARSH											
APPROVER											